



Data Sheet | Model: **Armorgard TransBank TRB3**



- 🚧 Fully welded, banded unit, for storing and transporting fuels and chemicals
- 🚧 High and low level ventilation
- 🚧 External fixing points to secure the unit
- 🚧 Over-centre clasp with padlock facility
- 🚧 Fitted with flame arrester gauze and built to the specification of 30 minute fire resistance
- 🚧 Suitable for storing fuels or chemicals
- 🚧 Fitted with hazardous warning signs
- 🚧 Designed for storing 3 x 20 litre cans

<b>Product</b>	Armorgard TransBank TRB3
<b>Internal dimensions</b>	620x415x510
<b>External dimensions (including protrusions)</b>	705x485x540
<b>Weight (kg)</b>	24
<b>Colour</b>	Pillar Box Red; RAL-3020
<b>Finished Coating</b>	Powder Coat with anti-corrosive undercoat
<b>Material</b>	Steel
<b>Material Thickness</b>	1.2mm
<b>Locking mechanism</b>	Overcentre catch with padlock facility
<b>Does it have Forklift Skids?</b>	No
<b>Does it have Gas Arms?</b>	No
<b>Newton Loading of Gas Arms</b>	N/A
<b>Safety stay</b>	No
<b>Quantity of keys supplied</b>	N/A
<b>Optional Extras Available</b>	50mm Brass Padlock
<b>Quantity of Shelves as standard</b>	0
<b>Are Castors standard or optional extra</b>	N/A
<b>How are the Castors fitted?</b>	N/A
<b>Sump capacity</b>	70
<b>Safety Signage</b>	Hazardous Goods Sign
<b>Fire resistant?</b>	Up to 30 minutes

